



8000T Cling

FEATURES

- Thermal transfer, vinyl static cling label
- Recommended for labeling applications requiring clean removability
- Available in white (66741RM)
- May be used in desktop printers
- For best performance use 3200 ribbon

MATERIAL CONSTRUCTION

Component	Description	Caliper
Facestock	White topcoated cling vinyl film	6.0 mil
Liner	40 lb. semi-bleached, kraft stock	2.5 mil
TOTAL ± 10%		8.5 mil

TEMPERATURE PERFORMANCE

Minimum Application Temperature	Service Temperature	Optimal Storage Conditions
32° F (0° C)	-40° F to 200° F (-40° C to 93° C)	72° F (22° C) at 50% RH

Expected Exterior Life

Two years

CHEMICAL RESISTANCE

Chemical	Suggested Ribbon		
	5555	6100	
Weak	Blood	●	●
	Body Fluid	●	●
	Salt Water	●	●
	Water	●	●
	Window Cleaner	●	●
Moderate	Alcohol	●	●
	Ammonia	●	●
	Bleach	●	●
	IPA	●	●
Harsh	Gasoline	●	●
	Grease	●	●
	Oil	●	●
Extreme	Acetone	●	●
	IR Reflow	●	●
	MEK	●	●
	TCE	●	●
	Xylene	●	●

● Recommended ● Test in Your Application NR Not Recommended

SUGGESTED APPLICATIONS

- Temporary parking identification



- Window labeling



- Work in process labeling



All products should be pre-tested to ensure it meets all intended requirements of specific end-use applications.

For more information, visit www.zebra.com/supplies

Product Performance and Suitability: The information contained in this document is to be used for guidance only and is not intended for use in setting specifications. All purchasers of Zebra products shall be solely responsible for independently determining if the product conforms to all requirements of their unique application.

NA and Corporate Headquarters | +1 800 423 0442 | inquiry4@zebra.com

©2018 ZIH Corp and/or its affiliates. All rights reserved. ZEBRA and the stylized Zebra head are trademarks of ZIH Corp, registered in many jurisdictions worldwide. All other trademarks are the property of their respective owners.